

Models 2310HD and 2310-Pro

Specifications

LCD Screen	23-inch diagonal TFT Active Matrix
Resolution	1366 x 768
Aspect Ratio	16:9
Contrast Ratio	700:1
H/V Viewing Angle	160° by 140°
Response Time	8 milliseconds
TV Formats	1080i, 720p, 480i, 480p
Input Connectors:	
RF	Antenna/CATV (NTSC, ATSC, QAM)
HDMI	HDMI Input x 2
Video Composite	S-Video x1 and Composite Video x1, L/R Audio Inputs x1
Video Component	YPbPr x1 plus Stereo Audio x 2
РС	15-pin D-sub VGA plus Stereo Audio
Control Set	RS232 Serial and Discrete IR Control (Model 2310-Pro only)
Audio Out	SPDIF Audio, Analog Headphone Jack
Speakers	5-watt x 2 channels, water resistant built-in speakers
Exterior	Powder-coated aluminum
Input Power	100-240 VAC, 50-60 Hz 2.2A Max
Operating Temp.	-24° to 122° F. (-31° to 50° C.) *
Non-op. Temp. (Off-mode with power applied)	-24° to 140° F. (-31° to 60° C.) The non-operating temperature feature requires power to be applied
Accessories Included	Water-resistant remote control with lithium battery Removable table top stand
TV Dimensions	23.51 in. W x 16.27 in. H x 4.90 in. D
Weight	22 lbs., 25 lbs. with feet
Shipping Dimensions	30.31 in. W x 19.49 in. H x 8.86 in. D
Shipping Weight	28 lbs.
Warranty	One-year, in-factory, parts and labor


SunBriteTV All-Weather Outdoor LCD Television

Designed with a durable **All-weather Environmental Feature-Set**, SunBriteTV engineers their televisions for permanent outdoor installation:

- The extra bright 23-inch HD 1366 x 768 LCD screen is integrated into an all-weather exterior that protects the internal components from rain, dirt, insects and scratches.
- Dual-fan Airflow System keeps the unit cool and dry in temperatures up to 122 degrees F.
- Internal Thermostatically-Controlled Heater protects TV in temperatures as low as -24 degrees F.
- Innovative Water-tight Cable Entry System with pass-through design keeps cables dry and allows for easy hook-ups.
- Anti-Reflective Window reduces glare, increases contrast and protects the LCD screen.
- The control buttons and remote control are also water- resistant.
- Remote Control Lock-out prevents unauthorized users from changing the programming.
- **Sleep Mode** automatically turns the TV to the Off mode when the signal is removed, and turns it back to On when the signal is restored.

Model 2310-Pro is the same as Model 2310HD with additional control features:

• RS232 and Discrete IR input connectors simplify control functions.



SunBriteTV Model 2310HD and 2310-Pro (All dimensions are in inches)

23.51 in. W x 16.27 in. H x 4.90 in. D Height dimension with table stand is 17.14 in. TV with optional wall mount measures 7.60 in. when folded flush against the wall.

Optional Accessories:

SB-CM20	Ceiling mount with tilt, includes adjustable extension column that provides 5" to 11" above unit to ceiling. Also includes 4" x 4" designer ceiling plate. Meets VESA standards.
SB-WM23	Articulating wall mount with tilt, swivel, pan and extends up to 9" from wall. Meets VESA standards.
SB-DP2332X	Deck/Planter pole (requires purchase of wall mount). Special order item.
SB-FMT23	RadioFM ^{IM} , transmits audio from TV to FM radio
SB-DC23	Outdoor TV dust cover

866.357.8688

www.sunbritetv.com

*Temperature range is for operation in shaded location.

Specifications may be subject to change.

Patent pending. All rights reserved. (C) 2009 SunBriteTV® LLC

5069 Maureen Lane, Unit A • Moorpark, CA 93021