MARQUIS. SERIES



2800MW10 Features & Information:

Product Information:

► Model No. 2800MW10

P/N 76239 (Light Ash) / P/N 762391 (Black) Custom Colors Avail. in Min. Quantities of 500

► Installation Includes

RJ25 Line Cords - 15ft./4.5m Handset Coil Cord - 9ft/2.25m

Optional Wall Mount Bracket (not included)

▶ Line, MW, and Ringer Specifications Line Voltage 24-52VDC (+/-)

Line Current 20mA-100mA

Switchable for 90VDC Neon or Low Voltage LED Applications

Ringer Equivalence - 0.5B

► Unit Dimensions

9.75"/24.38cm(I) 6.5"/16.25cm(w) 3.25"/8.13cm(h)

► Packaging Weight

MasterPack Quantities of 10 Units, 27lbs/12.25kg

FCC Part 68, FCC Part 15 & UL 1459 Ref. ADA/FCC Hearing Aid Compliant

Enhanced Features:

- ► Enhanced Single Line Operation
- ► Compatible with PABX Systems
- ► Soft Key Technology
- ► SteelTrap® Memory Technology no batteries required
- ► Convenient Data Port
- ▶ morePhone™ Automatic Overshipment for Qualified Orders Over 100 Phones
- ► Turnkey Telephone Modufications Available Ready for Instant Installallation
- ▶ Full Length Custom Tailored or Designer Faceplates
- ► Industrial Grade Construction with Matte Finish Design
- ► Non-Slip Base

Audio/Visual Features:

- ► Large, Bright Red, TouchLite ® Message Waiting Lamp
- ▶ 8 Step Handset Volume Control
- ► High/Low Ringer Volume Switch

Programming Features:

- ► One-Touch, TouchLite® Message Retrieval (programmable)
- ▶ 10 Guest Service Keys with Secure Programming
- ► Memory Key Entry Maximum 32 Digits
- ► Flash Key (submerged) 100 1000mS (programmable), 600mS Timing (default), Storable
- ► Pause Key (submerged) 1.0 5.0 Sec. (programmable), Storable
- ► Store Key (submerged)



5025 Galley Road Colorado Springs, CO 80915 1.800.462.9446 toll free 719.638.8821 tel. 719.638.8815 fax.

www.telematrixusa.com

TELEMATRIX.

Subject to change without notice. Please refer to telematrixusa.com for latest data.

V.10.05