# MARQUIS. SERIES
# 2800MWD

## Single Line Hospitality Telephone

### "Deluxe Feature Speakerphone"

▶ *Professional Quality Speakerphone*
▶ *10 Programmable Guest Service Keys*
▶ *Optional PassPort™ High Speed Access Port*
▶ *5 Year "no hassle" Warranty*



# 2800MWD Features & Information:

## Product Information:

▶ Model No. 2800MWD
   P/N 76339 (Light Ash) / P/N 763391 (Black)
   Custom Colors Avail. in Min. Quantities of 500
▶ Installation Includes
   RJ25 Line Cords - 15ft./4.5m
   Handset Coil Cord - 9ft/2.25m
   Optional Wall Mount Bracket (not included)
▶ Line, MW, and Ringer Specifications
   Line Voltage 24-52VDC (+/-)
   Line Current 20mA-100mA
   Switchable for 90VDC Neon or Low Voltage
     LED Applications
   Ringer Equivalence - 0.5B
▶ Unit Dimensions
   9.75"/24.38cm(l)  6.5"/16.25cm(w)  3.25"/8.13cm(h)
▶ Packaging Weight
   MasterPack Quantities of 10 Units, 29lbs/13.15kg
▶ Certifications
   FCC Part 68, FCC Part 15 & UL 1459 Ref.
   ADA/FCC Hearing Aid Compliant

*Subject to change without notice.*
*Please refer to telematrixusa.com for latest data.*
V.10.05

## Deluxe Features:

▶ Deluxe Single Line Speakerphone
▶ Compatible with PABX Systems
▶ Soft Key Technology
▶ PassPort™ High Speed Access Port Option
▶ SteelTrap® Memory Technology - no batteries required
▶ On-Hook Pre-Dialing on Memory Keys
▶ Convenient Data Port
▶ morePhone™ Automatic Overshipment for Qualified
   Orders Over 100 Phones
▶ Turnkey Telephone Modifications Available - Readiy for
   Instant Installation
▶ Full Length Custom Tailored or *Designer* Faceplates
▶ Industrial Grade Construction with Matte Finish Design
▶ Non-Slip Base

## Audio/Visual Features:

▶ Exceptional Quality Speakerphone
▶ Large, Bright Red, TouchLite® Message Waiting Lamp
▶ 8 Step Speaker and Handset Volume Control
▶ High/Low Ringer Volume Switch
▶ Speaker Key with LED On/Off Indication
▶ Mute Key with LED On/Off Indication

## Programming *Features:*

▶ One-Touch, TouchLite® Message Retrieval (programmable)
▶ 10 Guest Service Keys with Secure Programming
▶ Memory Key Entry - Maximum 32 Digits
▶ Flash Key (submerged) - 100 - 1000mS (programmable),
   600mS Timing (default), Storable
▶ Pause Key (submerged) - 1.0 - 5.0 Sec. (programmable),
   Storable
▶ Store Key (submerged)