

A white Teledex Diamond +S telephone is the central focus, resting on a light-colored wooden desk. The phone features a handset on the left, a speaker grille, and a keypad with various function buttons. In the background, a round analog clock with a white face and black hands is visible. To the right, a clear glass vase holds a purple flower. The overall scene is a classic office or hotel desk setting.

Teledex Díamond +S™

TELEDEX

The World's Leading Supplier of Guestroom Telephones

Diamond Speakerphone

Quality single-line integrated speakerphone for the hospitality industry.

FEATURES

- **Single-Line Integrated Speakerphone** with Volume Control providing hands-free conversation while working on a computer or taking notes.
- **Ten (10) Guest Service Buttons** allow guests to contact hotel services with the touch of a button.
- **ADA Handset Volume Boost**, with 3 distinct levels, compliant with HAC/VC and FCC requirements.
- **Data Port** for easy access to telephone line for laptop modem or fax machine use.
- **Raised Red Message Waiting** lens can be seen from any area in the guestroom.
- **Patented MultiX™ Message Waiting Circuitry** guarantees operation of up to 10 phones for suite applications with a new extra-bright message waiting lamp (up to 300% brighter).
- **Speaker On / Off Key** with red LED for easy activation of speakerphone calls.
- **Hold Key** with LED indicator places your caller on hold.
- **Hold Release** detection circuit releases calls on hold when the line is accessed by any telephone.
- **Mute Key** deactivates microphone during speakerphone and handset calls. A red LED indicates when mute is activated.
- **Redial Key** automatically redials the last number dialed.
- **Textured Finish** provides durable surface that resists smudges and scratches.
- **Full-length Paper Faceplate** allows customization and makes the telephone user-friendly.
- **Desk or Wall Mountable** providing flexibility in room placement.
- **Hidden Programming Key** eliminates arbitrary reprogramming of autodial keys.

SPECIFICATIONS

Standard Color	: Ash (Black Optional)	Operating Voltage	: 24 to 56 VDC Non Polarity
Footprint	: 6.25" x 9.0"	Signaling	: Standard 12 tone DTMF/Pulse
Weight	: 2.3 pounds	Flash Timing	: 600 ms
Packaging	: 12 per carton	Ringer Equivalence	: Z
Faceplate Size	: 8.75" x 3.13"	Cabling	: 1 pair minimum
FCC Specifications	: Meet or exceeds Part 15, Subpart J, Class A, Part 68	Registered Connector	: USOC RJ-11
Safety Standard	: ETL and CE	Handset	: Hearing Aid compatible Standard "K" type or Euro type
		Handset Cord	: 10 foot coil cord
		Line Cord	: 15 foot, 1 pair